



Excellence is our Passion

Flux Type	Alloy	Powder Size	Metal Load	Material IDH	Material Description	Packaging	Weight	Unit	Shelf Life (Days)	Condition(s)
-----------	-------	-------------	------------	--------------	----------------------	-----------	--------	------	-------------------	--------------

GC 10	SAC305	T4	88.5	2003721	LOCTITE GC 10 SAC305T4 885 53U	semco	600	G	30	at 40°C
GC 10	SAC305	T4	88.5	1993881	LOCTITE GC 10 SAC305T4 885 52U	jar	500	G	365	at 25°C ± 1.5°C
GC 10	SAC305	T4	88.5	2064242	LOCTITE GC 10 SAC305T4 885V 2U	Proflow	850	G	TBA	

GC 10	SAC305	T3	88.5	2023641	LOCTITE GC 10 SAC305T3 885 53U	semco	600	G	30	at 40°C
GC 10	SAC305	T3	88.5	2023628	LOCTITE GC 10 SAC305T3 885 52U	jar	500	G	365	at 25°C ± 1.5°C
GC 10	SAC305	T3	88.5	2064239	LOCTITE GC 10 SAC305T3 885V 2U	Proflow	850	G	TBA	

GC 3W	SAC305	T4	89.5	2040987	LOCTITE GC 3W SAC305T4 895V 53U	semco	600	G	30	at 40°C
GC 3W	SAC305	T4	89.5	2040989	LOCTITE GC 3W SAC305T4 895V 52U	jar	500	G	180	at 25°C ± 1.5°C

GC 3W	SAC305	T3	89.5	2041006	LOCTITE GC 3W SAC305T3 895V 53U	semco	600	G	30	at 40°C
GC 3W	SAC305	T3	89.5	2041005	LOCTITE GC 3W SAC305T3 895V 52U	jar	500	G	180	at 25°C ± 1.5°C